

AIRPORTS & AIRLINES

i420

COMPACT CHECK-IN COUNTER PRINTER

BAG TAG AND BOARDING PASS PRINTER
MAXIMUM OPERATIONAL EFFECTIVENESS
WITH CENTRALLY MANAGED SOFTWARE DISTRIBUTION



The logo for iVER, featuring the letters 'i', 'V', 'E', and 'R' in a stylized, blue, sans-serif font. The 'i' is smaller and positioned to the left of the 'V'. The 'V' and 'E' are connected, and the 'R' is to the right.



DESCRIPTION

The i420 is a multi-functional, direct thermal printer that facilitates the check-in process. It is specifically designed to be configured for both airlines' host systems and shared-use platforms. Based on standard Windows remote management tools, AEA applications can be very easily upgraded and reconfigured, ensuring 100% up-to-date printers in all locations at no extra cost. This unique capability avoids inconsistent versions, service disruptions and costly human on-site interventions.

KEY FEATURES

- Versatile single feed printer for boarding pass and bag tag
- Compact, simple and robust design
- Fast paper supply change
- Automatic set up of printing mode
- Centralized software management: AEA software upgrade and reconfiguration based on standard Windows remote management tools
- Configuration, diagnostics and monitoring via web browser
- CUSS compliant
- Certified with all major CUTE platforms
- AEA 2012 compliant
- Single paper roll holder (option)
- Boarding pass stacker (option)
- USB device

PRODUCT SPECIFICATIONS

Print method	Thermal direct
Print density	203 dpi
Supported protocol	AEA 2012 PC Driver
Barcode printing	All 1D and 2D barcodes including PDF417, Datamatrix, Aztec and QR code
Graphical user interface (optional)	2 lines LCD display with two-colour backlight (16 characters per line)
Connectivity	1 x USB device
Print speed	6 inches / second
Paper separation	Cutter or tear off
Paper loading	Automatic loading mechanism on paper detection
Paper feed	1 feed
Boarding pass paper & large receipt	Width: 24.5 to 83 mm (0.96" to 3.27") Length: 100 to 203 mm (3.94" to 8") Weight: 80 g/m ² to 200 g/m ²
Bag tag paper	Width: 24.5 to 83 mm (0.96" to 3.27") Length: 30 to 600 mm (1.18" to 23.62") Weight: 80 g/m ² to 200 g/m ²
Roll paper dimension (optional)	Diameter 150 mm maximum (5.91")
Dimensions (w x d x h)	206 x 149 x 170 mm (8.11" x 5.86" x 6.69") 206 x 380 x 230 mm with optional roll holder and roll (8.11" x 14.96" x 9.05")
Weight	2,7 kg (4.4 lbs)
Power	110 V/120 V or 200 V/230 V - 50 Hz/60 Hz
Operating temperature	5°C to 45°C (41°F to 113°F) (20% to 80%, non condensing) Storage -20°C to +60°C (-4°F to 140°F)
Reliability	
MTBF	53,000 hours
MCBF	300,000 cycles
Printhead	125 km printed or 100 million dot
Agency approvals	CE, CB, UL
Warranty	2 years

PRODUCT ACCESSORIES



Single bag tag roll holder



Boarding pass ATB stacker